

NTW Platform scales

General Specifications

- Capacities 30kg~600kg
- Display 52mm digit LCD display, with white LED backlight
- Keyboard 7 keys (Mechanical switch)
- Housing ABS plastic indicator
- Max. Divisions 2*3,000e
- Load cell excitation voltage 5V/150mA
- ADC Sigma delta
- ADC update $\leq 1/10$ second
- Operating Temp. $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), rechargeable battery (6V/4Ah)



- Applications: 1. Check weighing 2. Accumulation 3. Animal weighing 4. Peak hold
- Mild steel and die cast aluminum platforms available
- Battery provides up to 70 hours of continuous use (without backlight)
- Optional RS-232 interface
- Optional analogue output (0-10V/4-20mA)
- Optional setpoint output (HI/OK/LOW/BEEP)
- Optional blue tooth
- Optional initial-verification



NTW Platform scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
NTW-3024-30K-MR	30kg	5g/10g	2*3,000e	10.5kg	CE, OIML
NTW-4040-150K-MR	150kg	20g/50g	2*3,000e	16.4kg	CE, OIML
NTW-6060-300K-MR	300kg	50g/100g	2*3,000e	28kg	CE, OIML
NTW-8080-600K-MR	600kg	100g/200g	2*3,000e	75kg	CE, OIML

Options



Print formats

NO. :	1
GS :	4.240KG
DATE :	2012/03/07
TIME :	19:06:37
NO. :	1
GS :	4.235KG
DATE :	2012/03/07
TIME :	19:08:26
NO. :	2
NT :	4.235KG
TW :	1.810KG
GW :	6.045KG
DATE :	2012/03/07
TIME :	19:10:54
TOTAL	

NO :	3
Total :	12.705KG
DATE :	2012/03/07
TIME :	19:09:03
NO. :	1
GS :	4.235KG
TOTAL :	4.235KG
DATE :	2012/03/07
TIME :	19:10:48
NO. :	3
NT :	4.235KG
TW :	1.810KG
GW :	6.045KG
TOTAL :	12.705KG